



**NEW BUILDING SPECIFICATIONS**

36' X 48' X 10'4" POST & FRAME GARAGE

- -18" X 8" CONCRETE FOOTINGS (TYP.)  
(6184 LB CAP; 6080 LB COLUMN WT)
- ① 1-3'0" X 6'8" 9-LITE STEEL ENTRY DOOR
- ② 3-9 X 8 RAISED PANEL INSULATED OVERHEAD DOORS
- ③ 4-36" X 44" THERMALPANE SINGLE HUNG WINDOWS
- ☒ -3 PLY 2X6 GLU-LAM POSTS 8' OC.(TYP.)
- 2X6 TREATED SKIRT BOARD
- 2X4 SPRUCE WALL GIRTS & ROOF PERLINS 24" OC.
- 2-2X12 #1 SYP TRUSS CARRIERS @8' SPANS  
(970 PLF CAP; 760 PLF ROOF LOAD)
- PRE-ENGINEERED ROOF TRUSSES-  
4/12 PITCH, 48" OC, 30-5-5 LOADING
- TRUSS BRACING; 2X4 BOTTOM CHORD TIES 10' OC.
- 29 GA. G-100 PAINTED STEEL ROOFING & SIDING
- 12" EAVE OVERHANG W/ VENTED SOFFIT & FASCIA
- FLUSH GABLES
- 12" PAINTED STEEL RIDGECAP

**PROGRESS PRINT  
DO NOT USE FOR  
CONSTRUCTION**

FLOOR PLAN  
SCALE: 3/16" = 1'0"



SEAL

ALL INFORMATION SHOWN ON DRAWING IS THE PROPERTY OF SHIRK POLE BUILDINGS LLC. THE DRAWING MAY NOT BE COPIED WITHOUT PERMISSION. PERMISSION IS NOT GRANTED TO REPRODUCE OR TRANSMIT IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. DESIGNERS AS SHOWN PRIOR TO THIS DATE ARE NOT RESPONSIBLE FOR THIS DRAWING.

JOB NO: \_\_\_\_\_ SITE PLAN

SPE. REVIEW DRAWN BY: A. SHIRK  
CHECKED BY: \_\_\_\_\_

REVISIONS


DATE: \_\_\_\_\_

FLOOR PLAN

A.1